

Punta USB 2.0 TYPE C ETHERNET NETWORK ADAPTER



Features

- Portable Device.
- Compact Design.
- Plug and play Device.
- Enables a fast and stable data connection to Ethernet network.
- Interface: 10/100/1000Mbps RJ45 Ethernet & USB 2.0 Type -C
- Operating Temperature: 0 °C-40° C (32 °F-104 °F)
- Storage Temperature: -40 °C-70° C (-40 °F-58 °F)
- 1 Year warranty

[Read More](#)

SKU:

Price: ~~₹1,199.00~~ ₹839.00

Stock: instock

Categories: [USB to LAN](#)

Product Description

Introducing our high-performance Type C 2.0 Ethernet Network Adapter, designed to provide seamless and reliable network connectivity for your Type C 2.0-enabled devices. With this adapter, you can easily connect your devices to wired Ethernet networks, ensuring fast and stable internet connections. Our Type C 2.0 Ethernet Network Adapter utilizes the latest USB 2.0 technology, delivering lightning-fast data transfer speeds for optimal network performance. Experience high-speed data transmission with a maximum transfer rate of up to 5 Gbps, allowing for smooth streaming, quick file transfers, and lag-free online gaming. The compact and user-friendly design of our adapter makes it a perfect travel companion. Simply plug it into your Type C 2.0 port, and you can instantly connect to Ethernet networks without the hassle of complex installations or drivers. Enjoy broad compatibility with various devices and operating systems, including Windows, Mac OS, Linux, and more. Our adapter ensures seamless network connectivity across different platforms, keeping you connected and productive. Crafted with

premium materials, our Type C 2.0 Ethernet Network Adapter offers durability and long-lasting performance. We prioritize customer satisfaction and back our product with a generous warranty to ensure your peace of mind. **Features**

- Portable Device.
 - Compact Design.
 - Plug and play Device.
 - Enables a fast and stable data connection to Ethernet network.
 - Interface: 10/100/1000Mbps RJ45 Ethernet & USB 2.0 Type -C
 - Operating Temperature: 0 °C-40° C (32 °F-104 °F)
 - Storage Temperature: -40 °C-70° C (-40 °F-58 °F)
 - 1 Year warranty
-